



Stackable chair with upholstered seat and solid beech wood backrest and frame.

0.27 m3  
9.53 Ft
 5.8 kg  
12.79 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	760	460	500	485

Frame	Solid beech legs and interior frame.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Solid beech.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Soft-fiber  
Jacquard One  
Jacquard Three  
Citadel  
Sand  
Era  
Gravity  
Rivet  
Urban
- 2 Jacquard Two  
Solid & Stripes  
Loom One  
Circular One Pure Eco
- 3 Jacquard Four  
Medley  
Revive 1  
Natte  
Main Line Flax  
Loom Two  
Mezzo

- 4 Jacquard 4 Special  
Nexus  
Field 2  
Floyd  
Remix 3  
Heritage  
Savane  
Loom Three  
Loom Four  
Cura  
Oceanic
- 5 Silk  
Synergy  
Step  
Step Melange  
Blazer  
Melange Nap  
Glow  
Chili  
Noma  
Re-wool

- 6 Go check  
Swing  
Chartres  
Loom Five  
Zori  
Patio
- 7 Canvas 2  
Rime  
Select  
Clara 2
- 8 Capture  
Fiord 2  
Tonus 4  
Divina 3  
Lopi  
Domino
- 9 Divina MD  
Divina Melange 3  
Hallingdal 65  
Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia  
2 Silvertex  
3 Maglia  
4 Dolce
- 8 Ultraleather Original  
Ultraleather Linen  
Ultraleather Pearlized
- 9 Brisa Original  
Brisa Distressed  
Brisa Fresco  
Brisa Mokume  
Ultraleather Cora Outdoor  
Ultraleather Pony  
Ultraleather Pro  
Ultraleather Promessa  
Ultraleather Promessa Outdoor  
Ultraleather Dwell  
Ultratech EcoTech
- 10 Brisa Distressed Outdoor  
Ultraleather Distressed Outdoor  
Ultratech Helix  
Ultratech Wired

- 11 Ultraleather Reef Pro  
Ultraleather Volar Bio  
Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather  
 Piel de vaca de 1ª categoría
- L3

Polished full grain leather  
 Plena flor pulida
- L6

Aniline leather batique-effect.  
 Scandinavian cattle.  
 Piel anilina efecto batique.  
 Ganado escandinavo.

Leather



Wood finish  
Beech

RESISTANCE AND  
QUALITY

UNE-EN 16139:2013

FIREPROOF

B.S. 5852 Part 2 Crib V

UNI 9175 M-1

California Tech.Bulletin 117

SUSTAINABILITY

FSC

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard