



Chair with Eco thermo-polymer shell available in several colors or Pure Eco thermo-polymer (100% recycled) available in sand color and tubular steel cantilever base finished in polished chrome, white or black. Available options: Upholstered seat pad, upholstered hell pad, fully upholstered shell and parallel stitching upholstery. Fire retardant version available.

0.25 m3 19.5 kg
 8.83 Ft 42.99 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	780	455	495	475

Fabrics / Telas

- 1 Jacquard One
 Jacquard Three
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2 Jacquard Two
 *Loom One
 Circular One Pure Eco
- 3 Jacquard Four
 Medley
 Revive 1
 Main Line Flax
 Loom Two
 Mezzo

- 4 Jacquard 4 Special
 Nexus
 Floyd
 *Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7 Canvas 2
 Rime
 Select
 Clara 2
- 8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
 2 Silvertex
 3 Maglia
- 8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

* Only available with parallel stitching upholstery.
 Solo en tapizado con costuras paralelas.

Upholstery

Leather / Piel

- L1

High grade cow leather
 Piel de vaca de 1ª categoría
- L3

Polished full grain leather
 Plena flor pulida
- L6

Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather



Eco Thermo-
 polymer finish



Pure Eco Thermo-
 polymer finish



Steel finish



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard