




Counter stool with upholstered seat and back and injection swivel central base finished in polished aluminum, white or black.

0.26 m3 9.9 kg
9.18 Ft 21.83 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	890	650	500	500

Frame	Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3. Walnut back option.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accesories	Felt glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Upholstery	Fabrics / Telas			
	1 Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban	4 Jacquard 4 Special Nexus Field 2 Floyd Heritage Savane Loom Three Loom Four Cura Oceanic	6 Go check Swing Chartres Loom Five Zori Patio	Faux Leather / Ecopiel
	2 Jacquard Two Solid & Stripes Loom One Circular One Pure Eco	5 Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	7 Canvas 2 Rime Select Clara 2	1 Valencia 2 Silvertex 3 Maglia 4 Dolce 8 Ultraleather Original Ultraleather Linen Ultraleather Pearlized 9 Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro Ultraleather Promessa Ultraleather Promessa Outdoor Ultraleather Dwell Ultratech EcoTech 10 Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired
Leather	Leather / Piel			
	L1 High grade cow leather Piel de vaca de 1ª categoría			
	L3 Polished full grain leather Plena flor pulida			
	L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.			



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard