



Barstool with Eco thermo-polymer shell available in several colors or Pure Eco thermo-polymer (100% recycled) available in sand co l or and injection swivel central base finished in polished aluminum, white or black. Optional upholstered seat pad or upholstered s e l pad.

0.37 m3 8.5 kg 13.07 Ft 18.74 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,125	760	500	575

Fabrics / Telas

- 1
 Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2
 Jacquard Two
 Loom One
 Circular One Pure Eco
- 3
 Jacquard Four
 Medley
 Revive 1
 Main Line Flax
 Loom Two
 Mezzo

- 4
 Jacquard 4 Special
 Nexus
 Floyd
 Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5
 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6
 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7
 Canvas 2
 Rime
 Select
 Clara 2
- 8
 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9
 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel


- 1
 Valencia
 2
 Silvertex
 3
 Maglia
 4
 Dolce
 8
 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
 9
 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10
 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11
 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

- Leather / Piel
- L1 High grade cow leather
 Piel de vaca de 1ª categoría
- L3 Polished full grain leather
 Plena flor pulida
- L6 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather



Eco Thermo-
polymer finish



Pure Eco Thermo-
polymer finish



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard