



Upholstered ottoman.

0.69 m3

24.37 Ft

20 kg

44.09 Lbs

	Seat height	Width	Depth
Measures (mm)	430	1,600	800

Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 55 lb/ft3 and 88 lb/ft3.

Fabrics / Telas

- 1

Soft-fiber

Jacquard One

Jacquard Three

Citadel

Sand

Era

Gravity

Rivet

Urban
- 2

Jacquard Two

Solid & Stripes

Loom One

Circular One Pure Eco
- 3

Jacquard Four

Medley

Revive 1

Natte

Main Line Flax

Loom Two

Mezzo

- 4

Jacquard 4 Special

Nexus

Field 2

Floyd

Remix 3

Heritage

Savane

Loom Three

Loom Four

Cura

Oceanic
- 5

Silk

Synergy

Step

Step Melange

Blazer

Melange Nap

Glow

Chili

Noma

Re-wool

- 6

Go check

Swing

Chartres

Loom Five

Zori

Patio
- 7

Canvas 2

Rime

Select

Clara 2
- 8

Capture

Fiord 2

Tonus 4

Divina 3

Lopi

Domino
- 9

Divina MD

Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original

Ultraleather Linen

Ultraleather Pearlized
- 9

Brisa Original

Brisa Distressed

Brisa Fresco

Brisa Mokume

Ultraleather Cora Outdoor

Ultraleather Pony

Ultraleather Pro

Ultraleather Promessa

Ultraleather Promessa Outdoor

Ultraleather Dwell

Ultratech EcoTech
- 10

Brisa Distressed Outdoor

Ultraleather Distressed Outdoor

Ultratech Helix

Ultratech Wired

- 11

Ultraleather Reef Pro

Ultraleather Volar Bio

Ultratech Cove

Upholstery

Leather / Piel

- L1 High grade cow leather
Piel de vaca de 1ª categoría
- L3 Polished full grain leather
Plena flor pulida
- L6 Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard