



Upholstered ottoman.

0.14 m3

4.94 Ft

7.16 kg

15.79 Lbs

	Seat height	Width	Depth
Measures (mm)	430	620	400

Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Soft-fiber
Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2

Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3

Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4

Jacquard 4 Special
Nexus
Field 2
Floyd
Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5

Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6

Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7

Canvas 2
Rime
Select
Clara 2
- 8

Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9

Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9

Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10

Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11

Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Upholstery

Leather / Piel

- L1
 High grade cow leather
 Piel de vaca de 1ª categoría
- L3
 Polished full grain leather
 Plena flor pulida
- L6
 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard