



Fully upholstered ottoman.

0.17 m3

6 Ft

9.5 kg

20.94 Lbs

	Seat height	Width	Depth
Measures (mm)	380	700	510

Frame
 Curved beech plywood covered with flame retardant polyurethane flexible foam 55lb/ft3 and 88 lb/ft3 density.

Seat
 Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3.

Accesories
 Polypropylene, felt or steel glides.

Other materials
 Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2

Jacquard Two
 Solid & Stripes
 Loom One
 Circular One Pure Eco
- 3

Jacquard Four
 Medley
 Revive 1
 Natte
 Main Line Flax
 Loom Two
 Mezzo

- 4

Jacquard 4 Special
 Nexus
 Field 2
 Floyd
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5

Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6

Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7

Canvas 2
 Rime
 Select
 Clara 2
- 8

Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9

Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9

Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10

Brisa Distressed Outdoor
 Ultraleather Distressed Oudoor
 Ultratech Helix
 Ultratech Wired

- 11

Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather
Piel de vaca de 1ª categoría
- L3

Polished full grain leather
Plena flor pulida
- L6

Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard