



Stackable chair with Oak board seat and backrest and steel sled base finished in polished chrome, white or black. Optional Fully Upholstered shell or parallel upholstery stitching. Optional upholstered seat pad or upholstered shell pad.

0.3 m3

10.59 Ft

7.9 kg

17.42 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	810	460	520	555

Frame	Sled base of 0.47 inch diameter steel rod.
Seat	Oak board.
Back	Oak board.
Accesories	Felt glides.
Other materials	Zinc-nickel electrolyte screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Jacquard One

Jacquard Three

Citadel

Era

Gravity

Rivet

Urban
- 2

Jacquard Two

Circular One Pure Eco
- 3

Jacquard Four

Medley

Revive 1

Natte

Main Line Flax

Loom Two

Mezzo

- 4

Jacquard 4 Special

Nexus

Floyd

Heritage

Savane

Loom Three

Loom Four

Cura

Oceanic
- 5

Silk

Synergy

Step

Step Melange

Blazer

Melange Nap

Glow

Chili

Noma

Re-wool

- 6

Go check

Swing

Chartres

Zori

Patio
- 7

Canvas 2

Rime

Select

Clara 2
- 8

Capture

Fiord 2

Tonus 4

Divina 3

Lopi

Domino
- 9

Divina MD

Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original

Ultraleather Linen

Ultraleather Pearlized
- 9

Brisa Original

Brisa Distressed

Brisa Fresco

Brisa Mokume

Ultraleather Cora Outdoor

Ultraleather Pony

Ultraleather Pro

Ultraleather Promessa

Ultraleather Promessa Outdoor

Ultraleather Dwell

Ultratech EcoTech
- 10

Brisa Distressed Outdoor

Ultraleather Distressed Outdoor

Ultratech Helix

Ultratech Wired

- 11

Ultraleather Reef Pro

Ultraleather Volar Bio

Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather

Piel de vaca de 1ª categoría
- L3

Polished full grain leather

Plena flor pulida
- L6


Aniline leather batique-effect.

Scandinavian cattle.

Piel anilina efecto batique.

Ganado escandinavo.

Leather



Leather finish



Premium finish  
and wood  
lacquers



Wood finish Oak



Steel finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard