



Chair with upholstered seat and backrest and solid beech wood frame. Low back, Wider version.

0.35 m3
12.36 Ft

6.3 kg
13.89 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	875	460	500	565

Frame	Solid beech legs and interior frame.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accessories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

	Fabrics / Telas			Faux Leather / Ecopiel	
Upholstery	1 Soft-fiber Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban	4 Jacquard 4 Special Nexus Field 2 Floyd Remix 3 Heritage Savane Loom Three Loom Four Cura Oceanic	6 Go check Swing Chartres Loom Five Zori Patio	1 Valencia 2 Silvertex 3 Maglia 4 Dolce	11 Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove
	2 Jacquard Two Solid & Stripes Loom One Circular One Pure Eco	5 Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	7 Canvas 2 Rime Select Clara 2	8 Ultraleather Original Ultraleather Linen Ultraleather Pearlized	
	3 Jacquard Four Medley Revive 1 Natte Main Line Flax Loom Two Mezzo		8 Capture Fiord 2 Tonus 4 Divina 3 Lopi Domino	9 Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro Ultraleather Promessa Ultraleather Promessa Outdoor Ultraleather Dwell Ultratech EcoTech	
			9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	10 Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired	

Leather / Piel


- L1

High grade cow leather
Piel de vaca de 1ª categoría
- L3

Polished full grain leather
Plena flor pulida
- L6

Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Wood finish
 Beech



Premium finish
 and wood
 lacquers

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard