



Armchair with Pure Eco thermo-polymer (100% recycled), available in several colors and 4-star solid ash wood swivel base. Optional fully upholstered shell, upholstered seat pad, or upholstered shell pad.

0.27 m3 7 kg
9.53 Ft 15.43 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	750	460	640	600	560

Frame	Solid ash central swivel base.
Seat	Polypropylene shell covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Polypropylene shell covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Arms	Polypropylene shell covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accesories	Felt glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

1 Jacquard One
 Jacquard Three
 Era
 Gravity
 Rivet
 Urban

4 Jacquard 4 Special
 Nexus
 Floyd
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic

6 Go check
 Swing
 Chartres
 Zori
 Patio

7 Canvas 2
 Rime
 Select
 Clara 2

8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino

9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
 2 Silvertex
 3 Maglia

8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized

9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech

10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired


11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Leather / Piel

L1 High grade cow leather
 Piel de vaca de 1ª categoría

L3 Polished full grain leather
 Plena flor pulida

L6 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.





Eco Thermo-
polymer finish



Pure Eco Thermo-
polymer finish

RESISTANCE AND
QUALITY

UNE-EN 16139:2013

FIREPROOF

UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY

FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard