



Armchair with upholstered seat and backrest and 4-legs solid beech wood base.

0.29 m3 10.24 Ft 11.78 kg 25.97 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	825	465	640	590	560

Frame	4-legged solid beech base.
Seat	Shell made of flexible and fire resistant injected polyurethane foam with density of 132 lb/ft3.
Back	Shell made of flexible and fire resistant injected polyurethane foam with density of 132 lb/ft3.
Arms	Solid beech.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Jacquard One
 Jacquard Three
 Era
 Gravity
 Rivet
 Urban
- 2 Jacquard Two
 Loom One
 Circular One Pure Eco
- 3 Jacquard Four
 Medley
 Revive 1
 Natte
 Main Line Flax
 Loom Two
 Mezzo

- 4 Jacquard 4 Special
 Nexus
 Floyd
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7 Canvas 2
 Rime
 Select
 Clara 2
- 8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
 2 Silvertex
 3 Maglia
 4 Dolce
 8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Leather / Piel


- L1

High grade cow leather
Piel de vaca de 1ª categoría
- L3

Polished full grain leather
Plena flor pulida
- L6

Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Wood finish
 Beech



Premium finish
 and wood
 lacquers

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	B.S. 5852 Part 2 Crib V
SUSTAINABILITY	FSC
	ISO 14001
	level® 2 certified to ANSI/BIFMA e3 Standard