



Wider version. Intermediate back armchair with upholstered seat and back and aluminum swivel 4-star base with self-return system and finished in polished aluminum, white or black. Additional options include: tilting mechanism and back finished in walnut veneer.


0.49 m3 17.3 Ft 16.9 kg 37.26 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	1,000	460	640	670	670

Frame	Aluminum swivel 4-star base with self-return.
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3. Walnut back option.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accessories	Polypropylene, felt or steel glides. Tilting mechanism
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Upholstery	Fabrics / Telas			
	1 Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban	4 Jacquard 4 Special Nexus Field 2 Floyd Heritage Savane Loom Three Loom Four Cura Oceanic	6 Go check Swing Chartres Loom Five Zori Patio	Faux Leather / Ecopiel
	2 Jacquard Two Solid & Stripes Loom One Circular One Pure Eco	5 Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	7 Canvas 2 Rime Select Clara 2	
	3 Jacquard Four Medley Revive 1 Natte Main Line Flax Loom Two Mezzo		8 Capture Fiord 2 Tonus 4 Divina 3 Lopi Domino	
			9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	11 Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove
			10 Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired	

Leather	Leather / Piel			
	L1 High grade cow leather Piel de vaca de 1ª categoría			
	L3 Polished full grain leather Plena flor pulida			
	L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.			



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard