



Armchair with upholstered seat and backrest, steel oval cantilever base finished in polished chrome, white or black.

0.31 m3

10.95 Ft

14.2 kg

31.31 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	775	460	610	675	620

Frame	Solid steel cantilevered base. Polypropylene glides.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Jacquard One
Jacquard Three
Citadel
Era
Gravity
Rivet
Urban
- 2

Jacquard Two
Circular One Pure Eco
- 3

Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo
- 4

Jacquard 4 Special
Nexus
Floyd
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5

Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6

Go check
Swing
Chartres
Zori
Patio
- 7

Canvas 2
Rime
Select
Clara 2
- 8

Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9

Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9

Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10

Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11

Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Leather / Piel

- L1

High grade cow leather
Piel de vaca de 1ª categoría
- L3

Polished full grain leather
Plena flor pulida
- L6

Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Upholstery

Leather



Steel finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard