



Stackable chair with Oak board seat and backrest and solid beech wood. Wide versión. Option of Fully upholstered shell or upholstered shell pad.

0.409 m3
14.44 Ft
9.5 kg
20.94 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	785	450	550	570

FrameSolid ash legs and frame.

SeatOak board. Option of fully upholstered seat and back or upholstered shell pad covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.

AccesoriesPolypropylene, felt or steel glides.

Other materialsZinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Soft-fiber
 Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2 Jacquard Two
 Solid & Stripes
 Loom One
 Circular One Pure Eco
- 3 Jacquard Four
 Medley
 Revive 1
 Natte
 Main Line Flax
 Loom Two
 Mezzo

- 4 Jacquard 4 Special
 Nexus
 Field 2
 Floyd
 Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7 Canvas 2
 Rime
 Select
 Clara 2
- 8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
 2 Silvertex
 3 Maglia
 4 Dolce
 8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather
 Piel de vaca de 1ª categoría
- L3

Polished full grain leather
 Plena flor pulida
- L6

Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard