



Armchair with oak seat, back and frame available in finishes 306, 340 and 372. Wide version. Option of upholstered shell pad.

0.319 m³ 9 kg
 11.27 Ft 19.84 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	800	445	655	620	570

Frame Solid oak legs and frame.

Seat Oak board. Option of upholstered shell pad covered with flexible flame retardant polyurethane foam with density between 55 lb/ft³ and 88 lb/ft³.

Accessories Polypropylene, felt or steel glides.

Other materials Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Upholstery	Fabrics / Telas			Faux Leather / Ecopiel	
	1	4	6	1	11
	Soft-fiber Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban	Jacquard 4 Special Nexus Field 2 Floyd Remix 3 Heritage Savane Loom Three Loom Four Cura Oceanic	Go check Swing Chartres Loom Five Zori Patio	Valencia Silververtex Maglia Dolce	Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove
	Jacquard Two Solid & Stripes Loom One Circular One Pure Eco	Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	Canvas 2 Rime Select Clara 2	Ultraleather Original Ultraleather Linen Ultraleather Pearlized	
	Jacquard Four Medley Revive 1 Natte Main Line Flax Loom Two Mezzo		Capture Fiord 2 Tonus 4 Divina 3 Lopi Domino	Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro Ultraleather Promessa Ultraleather Promessa Outdoor Ultraleather Dwell Ultratech EcoTech	
			Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired	

Leather / Piel

- L1 High grade cow leather
Piel de vaca de 1ª categoría
- L3 Polished full grain leather
Plena flor pulida
- L6 Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard