



Barstool with upholstered seat and oak board backrest and solid beech wood frame.

0.25 m3

8.83 Ft

6.14 kg

13.54 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,015	780	470	470

Frame	Solid beech legs and interior frame.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Oak board.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Soft-fiber

Jacquard One

Jacquard Three

Citadel

Sand

Era

Gravity

Rivet

Urban
- 2

Jacquard Two

Solid & Stripes

Loom One

Circular One Pure Eco
- 3

Jacquard Four

Medley

Revive 1

Natte

Main Line Flax

Loom Two

Mezzo

- 4

Jacquard 4 Special

Nexus

Field 2

Floyd

Remix 3

Heritage

Savane

Loom Three

Loom Four

Cura

Oceanic
- 5

Silk

Synergy

Step

Step Melange

Blazer

Melange Nap

Glow

Chili

Noma

Re-wool

- 6

Go check

Swing

Chartres

Loom Five

Zori

Patio
- 7

Canvas 2

Rime

Select

Clara 2
- 8

Capture

Fiord 2

Tonus 4

Divina 3

Lopi

Domino
- 9

Divina MD

Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original

Ultraleather Linen

Ultraleather Pearlized
- 9

Brisa Original

Brisa Distressed

Brisa Fresco

Brisa Mokume

Ultraleather Cora Outdoor

Ultraleather Pony

Ultraleather Pro

Ultraleather Promessa

Ultraleather Promessa Outdoor

Ultraleather Dwell

Ultratech EcoTech
- 10

Brisa Distressed Outdoor

Ultraleather Distressed Outdoor

Ultratech Helix

Ultratech Wired

- 11

Ultraleather Reef Pro

Ultraleather Volar Bio

Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather

Piel de vaca de 1ª categoría
- L3

Polished full grain leather

Plena flor pulida
- L6


Aniline leather batique-effect.

Scandinavian cattle.

Piel anilina efecto batique.

Ganado escandinavo.

Leather



Leather finish



Wood finish  
Beech



Premium finish  
and wood  
lacquers

RESISTANCE AND  
QUALITY
 UNE-EN 16139:2013

FIREPROOF
 UNE-EN 1021-1:2006  
 B.S. 5852 Part 2 Crib V  
 UNI 9175 M-1  
 California Tech.Bulletin 117  
 BKZ 5.2

SUSTAINABILITY
 FSC  
 ISO 14001  
 level® 2 certified to ANSI/BIFMA e3 Standard