



Barstool with Oak board shell and injection swivel central base, adjustable height and finished in polished aluminum, white or black.

0.35 m3

12.36 Ft

7.5 kg

16.53 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	920	630	595	560

Frame	Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accesories	Felt glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

1 Jacquard One  
 Jacquard Three  
 Era  
 Gravity  
 Rivet  
 Urban

4 Jacquard 4 Special  
 Nexus  
 Floyd  
 Heritage  
 Savane  
 Loom Three  
 Loom Four  
 Cura  
 Oceanic

6 Go check  
 Swing  
 Chartres  
 Zori  
 Patio

7 Canvas 2  
 Rime  
 Select  
 Clara 2

8 Capture  
 Fiord 2  
 Tonus 4  
 Divina 3  
 Lopi  
 Domino

9 Divina MD  
 Divina Melange 3  
 Hallingdal 65  
 Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia  
 2 Silvertex  
 3 Maglia

8 Ultraleather Original  
 Ultraleather Linen  
 Ultraleather Pearlized

9 Brisa Original  
 Brisa Distressed  
 Brisa Fresco  
 Brisa Mokume  
 Ultraleather Cora Outdoor  
 Ultraleather Pony  
 Ultraleather Pro  
 Ultraleather Promessa  
 Ultraleather Promessa Outdoor  
 Ultraleather Dwell  
 Ultratech EcoTech

10 Brisa Distressed Outdoor  
 Ultraleather Distressed Outdoor  
 Ultratech Helix  
 Ultratech Wired


11 Ultraleather Reef Pro  
 Ultraleather Volar Bio  
 Ultratech Cove

Leather / Piel

L1 High grade cow leather  
 Piel de vaca de 1ª categoría

L3 Polished full grain leather  
 Plena flor pulida

L6 Aniline leather batique-effect.  
 Scandinavian cattle.  
 Piel anilina efecto batique.  
 Ganado escandinavo.





Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard