



Barstool with upholstered shell and steel sled base finished in polished chrome, white or black.

0.31 m3

10.95 Ft

12.6 kg

27.78 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,005	780	500	465

Frame	Sled base of 0.47 inches diameter steel rod.
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Jacquard One
- Jacquard Three

Citadel

Sand

Era

Gravity

Rivet

Urban
- 2

Jacquard Two
- Solid & Stripes

Loom One

Circular One Pure Eco
- 3

Jacquard Four
- Medley

Revive 1

Natte

Main Line Flax

Loom Two

Mezzo

- 4

Jacquard 4 Special
- Nexus

Field 2

Floyd

Heritage

Savane

Loom Three

Loom Four

Cura

Oceanic
- 5

Silk
- Synergy

Step

Step Melange

Blazer

Melange Nap

Glow

Chili

Noma

Re-wool

- 6

Go check
- Swing

Chartres

Loom Five

Zori

Patio
- 7

Canvas 2
- Rime

Select

Clara 2
- 8

Capture
- Fiord 2

Tonus 4

Divina 3

Lopi

Domino
- 9

Divina MD
- Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original
- Ultraleather Linen

Ultraleather Pearlized
- 9

Brisa Original
- Brisa Distressed

Brisa Fresco

Brisa Mokume

Ultraleather Cora Outdoor

Ultraleather Pony

Ultraleather Pro

Ultraleather Promessa

Ultraleather Promessa Outdoor

Ultraleather Dwell

Ultratech EcoTech
- 10

Brisa Distressed Outdoor
- Ultraleather Distressed Outdoor

Ultratech Helix

Ultratech Wired

- 11

Ultraleather Reef Pro
- Ultraleather Volar Bio

Ultratech Cove

Upholstery

Leather / Piel

L1 High grade cow leather
Piel de vaca de 1ª categoría

L3 Polished full grain leather
Plena flor pulida

L6 Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Steel finish

RESISTANCE AND QUALITY

UNE-EN 16139:2013

FIREPROOF

UNE-EN 1021-1:2006

B.S. 5852 Part 2 Crib V

UNI 9175 M-1

California Tech.Bulletin 117

BKZ 5.2

SUSTAINABILITY

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard