



Barstool with Pure Eco thermo-polymer (100% recycled) available in several colors and steel sled base finished in polished chrome, white or black. Optional upholstered seat pad or upholstered shell pad.

0.39 m3 12.6 kg
13.77 Ft 27.78 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,125	760	530	575

Frame	Sled base of 0.47 inches diameter steel rod.
Seat	Fiber glass reinforced polypropylene seat and back shell.
Back	Fiber glass reinforced polypropylene seat and back shell.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2 Jacquard Two
 Loom One
 Circular One Pure Eco
- 3 Jacquard Four
 Medley
 Revive 1
 Main Line Flax
 Loom Two
 Mezzo

- 4 Jacquard 4 Special
 Nexus
 Floyd
 Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7 Canvas 2
 Rime
 Select
 Clara 2
- 8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
 2 Silvertex
 3 Maglia
 4 Dolce
- 8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather
 Piel de vaca de 1ª categoría
- L3

Polished full grain leather
 Plena flor pulida
- L6

Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather

<div>6000</div> <div>RAL 9003</div> <div>White</div>	<div>6002</div> <div>NCS 2005-Y20R</div> <div>Sand</div>	<div>6012</div> <div>NCS 4005-Y20R</div> <div>Basalt grey</div>	<div>6006</div> <div>RAL 9005</div> <div>Black</div>	<div>6013</div> <div>NCS S 6502-B</div> <div>Dark grey</div>	<div>6015</div> <div>NCS 4020-Y20R</div> <div>Camel brown</div>	<div>6016</div> <div>Pantone 5445U</div> <div>Water blue</div>	<div>6017</div> <div>Pantone 5655U</div> <div>Marine green</div>	<div>6018</div> <div>Pantone 7528U</div> <div>Terracotta brown</div>	<div>6019</div> <div>RAL 3009</div> <div>Oxide red</div>
--	--	---	--	--	---	--	--	--	--

Eco Thermo-
 polymer finish

<div>6002</div> <div>NCS 2005-Y20R</div> <div>Sand</div>
--

Pure Eco Thermo-
 polymer finish



Steel finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard