



Hula 46. Counter stool with upholstered shell and injection swivel central base finished in different colors.

0.17 m3
6 Ft
7 kg
15.43 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	760	680	460	500

Back	Upholstered back with flame retardant polyurethane flexible foam with a density between 25 kg/m3 and 40 kg/m5
Accesories	Felt glide.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Frame	Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
Seat	Upholstered seat with flame retardant polyurethane flexible foam with a density between 55 lb/ft3 and 88 lb/ft3.
Leather	<div> <div>Leather / Piel</div> <div> <div>L1</div> <div>High grade cow leather</div> <div>Piel de vaca de 1ª categoría</div> </div> <div> <div>L3</div> <div>Polished full grain leather</div> <div>Plena flor pulida</div> </div> <div> <div>L6</div> <div>Aniline leather batique-effect.</div> <div>Scandinavian cattle.</div> <div>Piel anilina efecto batique.</div> <div>Ganado escandinavo.</div> </div> </div>



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard