



Hula 46. Barstool with upholstered seat or oak wood and injection swivel central base, adjustable height, and finished in different colors.

0.14 m³ 6.7 kg
4.94 Ft 14.77 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	655	680	485	460

Frame	Injected aluminium swivel central base. Rotating system integrated into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------

Seat	Upholstered seat with flame retardant polyurethane flexible foam with a density between 55 lb/ft3 and 88 lb/ft3, oak or walnut wood.
-------------	--------------------------------------------------------------------------------------------------------------------------------------

Accessories	Felt glide.
--------------------	-------------

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Leather / Piel

L1 High grade cow leather
Piel de vaca de 1ª categoría

L3 Polished full grain leather
Plena flor pulida

L6 Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

Premium finish
 and wood
 lacquers



Wood finish Oak



Aluminum finish



RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard