



Counter stool with an Oak board seat and backrest and a solid Oak wood frame. Optional: Upholstered seat pad.

0.22 m3

7.77 Ft

3.9 kg

8.6 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	775	640	390	450

Frame	Solid oak legs and interior frame.
Seat	Oak board.
Back	Oak board.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1

Soft-fiber

Jacquard One

Jacquard Three

Citadel

Sand

Era

Gravity

Rivet

Urban
- 2

Jacquard Two

Solid & Stripes

Loom One

Circular One Pure Eco
- 3

Jacquard Four

Medley

Revive 1

Natte

Main Line Flax

Loom Two

Mezzo

- 4

Jacquard 4 Special

Nexus

Field 2

Floyd

Remix 3

Heritage

Savane

Loom Three

Loom Four

Cura

Oceanic
- 5

Silk

Synergy

Step

Step Melange

Blazer

Melange Nap

Glow

Chili

Noma

Re-wool

- 6

Go check

Swing

Chartres

Loom Five

Zori

Patio
- 7

Canvas 2

Rime

Select

Clara 2
- 8

Capture

Fiord 2

Tonus 4

Divina 3

Lopi

Domino
- 9

Divina MD

Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original

Ultraleather Linen

Ultraleather Pearlized
- 9

Brisa Original

Brisa Distressed

Brisa Fresco

Brisa Mokume

Ultraleather Cora Outdoor

Ultraleather Pony

Ultraleather Pro

Ultraleather Promessa

Ultraleather Promessa Outdoor

Ultraleather Dwell

Ultratech EcoTech
- 10

Brisa Distressed Outdoor

Ultraleather Distressed Outdoor

Ultratech Helix

Ultratech Wired

- 11

Ultraleather Reef Pro

Ultraleather Volar Bio

Ultratech Cove

Upholstery

Leather / Piel

- L1

High grade cow leather
Piel de vaca de 1ª categoría
- L3

Polished full grain leather
Plena flor pulida
- L6

Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Premium finish
and wood
lacquers



Wood finish Oak

RESISTANCE AND
QUALITY
 UNE-EN 16139:2013

FIREPROOF
 UNE-EN 1021-1:2006
 B.S. 5852 Part 2 Crib V
 UNI 9175 M-1
 California Tech.Bulletin 117

SUSTAINABILITY
 FSC
 ISO 14001
 level® 2 certified to ANSI/BIFMA e3 Standard