



Low back lounge chair with upholstered seat and backrest, steel sled base finished in polished chrome, white or black.

0.46 m3

16.24 Ft

20 kg

44.09 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	800	430	480	720	720

Frame	Sled base of 0.47 inches diameter steel rod. Polypropylene glides.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 55 lb/ft3 and 88 lb/ft3.
Back	Beech plywood shell with flexible flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3.
Accessories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Upholstery

Leather

Fabrics / Telas		Faux Leather / Ecopiel	
1	Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban	6	Go check Swing Chartres Loom Five Zori Patio
2	Jacquard Two Solid & Stripes Loom One Circular One Pure Eco	7	Canvas 2 Rime Select Clara 2
3	Jacquard Four Medley Revive 1 Natte Main Line Flax Loom Two Mezzo	8	Capture Fiord 2 Tonus 4 Divina 3 Lopi Domino
4	Jacquard 4 Special Nexus Field 2 Floyd Heritage Savane Loom Three Loom Four Cura Oceanic	9	Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3
5	Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	10	Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired
6		11	Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove
Leather / Piel			
L1	High grade cow leather Piel de vaca de 1ª categoría		
L3	Polished full grain leather Plena flor pulida		
L6	Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.		



Steel finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard