



Reposapiés completamente tapizado.

0,17 m3 9,5 kg 6 Ft 20,94 Lbs

	Altura de asiento	Ancho	Anchura
Medidas (mm)	380	700	510

Estructura Tablero contrachapado curvado de haya recubierto de espuma flexible ignífuga de poliuretano de densidad entre 25kg/m3 y 40 kg/m3.

Asiento Tapizado recubierto de espuma flexible ignífuga de densidad entre 25kg/m3 y40 kg/m3.

Accesorios Tacos deslizantes de polipropileno, fieltro o acero.

Otros materiales Tornillos de zinc-níquel electrolítico. Grapas galvanizadas. Cola de acetato de polivinilo.

Fabrics / Telas

- 1

Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2

Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3

Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4

Jacquard 4 Special
Nexus
Field 2
Floyd
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5

Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6

Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7

Canvas 2
Rime
Select
Clara 2
- 8

Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9

Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1

Valencia
- 2

Silvertex
- 3

Maglia
- 4

Dolce
- 8

Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9

Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10

Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11

Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Tapicería

Leather / Piel

L1 High grade cow leather
 Piel de vaca de 1ª categoría

L3 Polished full grain leather
 Plena flor pulida

L6 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Piel

CERTIFICADOS DE CALIDAD
 UNE-EN 16139:2013

CERTIFICADOS DE IGNIFUGABILIDAD
 UNE-EN 1021-1, UNE-EN 1021-2
 B.S. 5852 Part 2 Crib 5
 UNI 9175 M-1
 California Tech.Bulletin 117
 BKZ 5.2

CERTIFICADOS DE SOSTENIBILIDAD
 ISO 14001
 level® 3 cert. to ANSI/BIFMA