Andreu World

SI1864 Flex Executive

Piergiorgio Cazzaniga



Silla de respaldo intermedio con carcasa tapizada y base central giratoria de termopolímero Eco de 5 ruedas, regulable en altura y acabado negro. Opciones disponibles: Tapizado con costuras paralelas, sistema basculante y respaldo en madera de nogal.

Fabrics / Telas

Medidas

Altura de respaldo	Altura de asiento	Ancho	Anchura
990	440	665	620

Faux Leather / Ecopiel

(mm)

1 Jacquard One Jacquard Three Sand Era	4 Jacquard 4 Special Nexus Floyd *Remix 3	6 Go check Swing Chartres Loom Five	 Valencia Silvertex Maglia 	11 Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove
Gravity Rivet Urban	Rivet Savane Urban Loom Three	Zori Patio 7 Canvas 2	8 Ultraleather Original Ultraleather Linen Ultraleather Pearlized	
Loom Four Cura Oceanic	Rime Select Clara 2	 9 Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume 	* Only available with parallel stitching upholstery.	
*Loom One Circular One Pure Eco	5 Silk Synergy Step	8 Capture Fiord 2 Tonus 4 Divina 3	Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro	Solo en tapizado con costuras paralelas.
3 Jacquard Four Medley Revive 1 Main Line Flax	Step Melange Blazer Melange Nap Glow	Lopi Domino 9 Divina MD	Ultraleather Promessa Ultraleather Promessa Out Ultraleather Dwell Ultratech EcoTech	door
Loom Two Chili Mezzo Noma Re-wool	Chili Noma	Divina Melange 3 Hallingdal 65 Steelcut Trio 3	10 Brisa Distressed Outdoor Ultraleather Distressed Ou Ultratech Helix Ultratech Wired	door

Tapicería

Andreu World

SI1864 Flex Executive

Piergiorgio Cazzaniga

Leather / Piel

- L1 High grade cow leather Piel de vaca de 1ª categoría
- L3 Polished full grain leather Plena flor pulida
- L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.

Piel



Acabado de Termopolímero Eco

CERTIFICADOS DE CALIDAD

UNE-EN 16139:2013

CERTIFICADOS

UNE-EN 1021-1, UNE-EN 1021-2

IGNIFUGABILIDAD

B.S. 5852 Part 2 Crib 5

California Tech.Bulletin 117

BKZ 5.2

CERTIFICADOS DE

ISO 14001

SOSTENIBILIDAD

level® 3 cert. to ANSI/BIFMA